

isc N-Channel MOSFET Transistor

FQPF7N80C

FEATURES

- Drain-source on-resistance: RDs(on) ≤ 1.9 Ω @10V
- Fast Switching Speed
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS


• High efficiency switch mode power supplies.

• ABSOLUTE MAXIMUM RATINGS(Ta=25°C)

SYMBOL	PARAMETER	VALUE	UNIT	
V _{DSS}	Drain-Source Voltage	800	V	
V _{GS}	Gate-Source Voltage	±30	V	
ID	Drain Current-Continuous	6.6	А	
I _{DM}	Drain Current-Single Pulsed	26.4	А	
P _D	Total Dissipation @T _C =25°C	56	W	
Tj	Operating Junction Temperature	-55~150	°C	
T _{stg}	Storage Temperature	-55~150	°C	

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT	
Rth(j-c)	Juction-to-case thermal resistance	2.23	°C/W	



isc website: www.iscsemi.cn

1



isc N-Channel MOSFET Transistor

FQPF7N80C

ELECTRICAL CHARACTERISTICS

$T_c=25^{\circ}C$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	ТҮР	МАХ	UNIT
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0V; I _D = 250 μ A	800			V
V _{GS} (th)	Gate Threshold Voltage	V _{DS} = V _{GS} ; I _D = 250 μ A	3		5	V
R _{DS(on)}	Drain-Source On-Resistance	V _{GS} =10V; I _D =3.3A			1.9	Ω
lgss	Gate-Source Leakage Current	V _{GS} = ±30V;V _{DS} = 0V			±100	nA
I _{DSS}	Drain-Source Leakage Current	V _{DS} = 800V; V _{GS} = 0V			10	μA
V _{SD}	Diode forward on voltage	Is = 6.6A, V _{GS} = 0 V			1.4	V



NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications. ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.

isc website: www.iscsemi.cn