



## P-Channel MOSFET

### AO3407A (KO3407A)

#### ■ Features

- $V_{DS} (V) = -30V$
- $I_D = -4.3 A (V_{GS} = -10V)$
- $R_{DS(ON)} < 48m\Omega (V_{GS} = -10V)$
- $R_{DS(ON)} < 78m\Omega (V_{GS} = -4.5V)$



#### ■ Absolute Maximum Ratings $T_a = 25^\circ C$

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	$V_{DS}$	-30	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	
Continuous Drain Current	$I_D$	$T_A = 25^\circ C$	A
		$T_A = 70^\circ C$	
Pulsed Drain Current	$I_{DM}$	-25	
Power Dissipation	$P_D$	$T_A = 25^\circ C$	W
		$T_A = 70^\circ C$	
Thermal Resistance.Junction- to-Ambient	$R_{thJA}$	$t \leq 10s$	$^\circ C/W$
		Steady-State	
Thermal Resistance.Junction- to-Lead	$R_{thJL}$	80	
Junction Temperature	$T_J$	150	$^\circ C$
Junction Storage Temperature Range	$T_{stg}$	-55 to 150	

## P-Channel MOSFET

### AO3407A (KO3407A)

#### ■ Electrical Characteristics Ta = 25°C

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit	
Drain-Source Breakdown Voltage	V <sub>DSS</sub>	I <sub>D</sub> =-250 μA, V <sub>GS</sub> =0V	-30			V	
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>DS</sub> =-30V, V <sub>GS</sub> =0V			-1	μA	
		V <sub>DS</sub> =-30V, V <sub>GS</sub> =0V, T <sub>J</sub> =55°C			-5		
Gate-Body leakage current	I <sub>GSS</sub>	V <sub>DS</sub> =0V, V <sub>GS</sub> =±20V			±100	nA	
Gate Threshold Voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> =V <sub>GS</sub> I <sub>D</sub> =-250 μA	-1.4		-2.4	V	
Static Drain-Source On-Resistance	R <sub>Ds(on)</sub>	V <sub>GS</sub> =-10V, I <sub>D</sub> =-4.3A			48	mΩ	
		V <sub>GS</sub> =-10V, I <sub>D</sub> =-4.3A T <sub>J</sub> =125°C			68		
		V <sub>GS</sub> =-4.5V, I <sub>D</sub> =-3A			78		
On state drain current	I <sub>D(ON)</sub>	V <sub>GS</sub> =-10V, V <sub>DS</sub> =-5V	-25			A	
Forward Transconductance	g <sub>FS</sub>	V <sub>DS</sub> =-5V, I <sub>D</sub> =-4.3A		10		S	
Input Capacitance	C <sub>iss</sub>	V <sub>GS</sub> =0V, V <sub>DS</sub> =-15V, f=1MHz		520		pF	
Output Capacitance	C <sub>oss</sub>			100			
Reverse Transfer Capacitance	C <sub>rss</sub>			65			
Gate resistance	R <sub>g</sub>	V <sub>GS</sub> =0V, V <sub>DS</sub> =0V, f=1MHz	3.5		11.5	Ω	
Total Gate Charge (10V)	Q <sub>g</sub>	V <sub>GS</sub> =-10V, V <sub>DS</sub> =-15V, I <sub>D</sub> =-4.3A		9.2	11	nC	
Total Gate Charge (4.5V)				4.6	6		
Gate Source Charge			Q <sub>gs</sub>		1.6		
Gate Drain Charge			Q <sub>gd</sub>		2.2		
Turn-On DelayTime	t <sub>d(on)</sub>	V <sub>GS</sub> =-10V, V <sub>DS</sub> =-15V, R <sub>L</sub> =3.5Ω, R <sub>GEN</sub> =3Ω		7.5		ns	
Turn-On Rise Time	t <sub>r</sub>			5.5			
Turn-Off DelayTime	t <sub>d(off)</sub>			19			
Turn-Off Fall Time	t <sub>f</sub>			7			
Body Diode Reverse Recovery Time	t <sub>rr</sub>	I <sub>F</sub> =-4.3A, di/dt=100A/μs		11		nC	
Body Diode Reverse Recovery Charge	Q <sub>rr</sub>			5.3			
Maximum Body-Diode Continuous Current	I <sub>S</sub>				-2	A	
Diode Forward Voltage	V <sub>SD</sub>	I <sub>S</sub> =-1A, V <sub>GS</sub> =0V			-1	V	

\* The static characteristics in Figures 1 to 6 are obtained using <300us pulses, duty cycle 0.5% max.

#### ■ Marking

Marking	X7**
---------	------

## P-Channel MOSFET AO3407A (KO3407A)

■ Typical Characteristics




Fig 1: On-Region Characteristics (Note E)




Figure 2: Transfer Characteristics (Note E)




Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)




Figure 4: On-Resistance vs. Junction Temperature (Note E)




Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)




Figure 6: Body-Diode Characteristics (Note E)

## P-Channel MOSFET AO3407A (KO3407A)

■ Typical Characteristics

